

Kitemark™ Certificate

This is to certify that:

Stevly UPVC Supply Centre Limited
T/A Stevly Windows
Units E & F Bowen Industrial Estate
Aberbargoed
Bargoed
Caerphilly
CF81 9EP
United Kingdom

Holds Certificate Number:

KM 620174

In respect of:

BS 7412
PVC-U Window Fabricator

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.



For and on behalf of BSI:

Shahm Barhom, Group Product Certification Director

First Issued: 2014-11-30

Latest Issue: 2025-01-22

Effective Date: 2025-02-08

Expiry Date: 2028-02-07



Page: 1 of 3

Kitemark™ Certificate

No. KM 620174

BS 7412:2007 - Plastics windows made from unplasticized polyvinyl chloride (PVC-U) extruded hollow profiles.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Linar Limited under Certificate Number KM 522037.

Linar Chamfered/Sculptured PVC-U Window System

Fabrication and Installation:	Fabricated and installed in accordance with the latest issue(s) of the following Linar Limited controlled manual(s): Linar Limited Fabrication Manual
System description:	The windows are double glazed only, internally or externally beaded*, multipoint locking only, with welded and/or mechanically fixed transoms/mullions, tee and/or cruciform joints (* dependent on window type).
Ventilation:	None
Window Types:	Casement windows Tilt/turn windows Fixed windows Multilight windows comprising opening light(s) and/or fixed light(s)

First Issued: 2014-11-30
Latest Issue: 2025-01-22

Effective Date: 2025-02-08
Expiry Date: 2028-02-07

Kitemark™ Certificate

No. KM 620174

Size Limitations and Performance Characteristics

Linlar Chamfered/Sculptured PVC-U Window System

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Perimeter (mm) - Maximum	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightnes classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1
Sash dimensions for windows with approved sash profiles:								
Projecting top hungs	1242	1242	-	-	2	7A	3	1200
Projecting side hungs	642	1242	-	-	3	7A	3	1200
Tilt/turns	1402	1402	-	-	2	6A	3	1200
Overall dimensions for window with approved outer frame profiles:								
Fixeds	3000	3000	10000	-	4	5A	2	800
Overall dimensions for windows with approved outer frame & transom/mullion profiles:								
Multilights Unreinforced T/M	1800	1800	5600	1000	4	7A	3	800
Multilights, LAR021 T/M reinforcement	1800	1800	6800	1800	4	9A	2	800
Multilights, LAR021 T/M reinforcement	2700	2700	8000	1300	2	8A	2	800
Multilights, LSR021 T/M reinforcement	1800	1800	6800	1800	4	E1050	2	800
Multilights, LSR021 T/M reinforcement	2700	2700	9000	1800	4	7A	2	800

BS 7412:2007 has been issued by BSI under a flexible accreditation scope

First Issued: 2014-11-30

Latest Issue: 2025-01-22

Effective Date: 2025-02-08

Expiry Date: 2028-02-07

Page: 3 of 3

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.